

Page 1/8

Safety data sheet according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SICCATIVE COURTRAI (PALE) 030
- · Article number: 24285030
- · **UFI:** 8F10-C0X9-G00H-XEVW
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified use: Siccative for artists' oilcolour

1.3 Manufacturer/Supplier:

Royal Talens P.O.Box 4

NL-7300 AA Apeldoorn Tel. +31 (0)55 5274700

· Further information obtainable from:

Regulatory Affairs safety@royaltalens.com

· 1.4 Emergency telephone number:

Great Britain: National Poisons Information Service (Birmingham) tel. (44) (0) 1215074123

Ireland: National Poisons Information Centre (Dublin) tel. 35 3 18379966

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS08

(Contd. on page 2)

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labelling:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P271 Use only outdoors or in a well-ventilated area.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P501 Dispose of contents/container to hazardous waste collection point.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
EC/List number: 919-857-5	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2%	70-80%
Reg.nr.: 01-2119463258-33	aromatics	
	♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336	
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, $< 2\%$	10-20%
Reg.nr.: 01-2119457273-39	aromatics	
	♦ Asp. Tox. 1, H304	
CAS: 106705-37-7	Strontium neodecanoate	5-10%
	♠ Acute Tox. 4, H302	
CAS: 67-63-0	propan-2-ol	1-2.5%
EINECS: 200-661-7	♠ Flam. Liq. 2, H225; ♠ Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GD

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

(Contd. of page 2)

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: CO2, powder, water haze, foam
- · For safety reasons unsuitable extinguishing agents: Water spray
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

- · 6.2 Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect from heat.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · Storage class: -
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

	ts with limit values that require monitoring a copan-2-ol (1-2.5%)	T
WEL Shor	rt-term value: 1250 mg/m³, 500 ppm g-term value: 999 mg/m³, 400 ppm	
DNELs		
Hydrocarl	oons, C9-C11, n-alkanes, isoalkanes, cyclics,	<2% aromatics
Oral	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
Dermal	DNEL,long term (chronic) - systemic effects	125 mg/kg bw/day (Consumer)
		208 mg/kg bw/day (Employee)
Inhalative	DNEL,long term (chronic) - systemic effects	185 mg/m3 (Consumer)
	= · / • • • • • • • • • • • • • • • • • •	871 mg/m3 (Employee)

(Contd. on page 4)

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

				(Contd. of page 3)
67-63-0 pr	opan-2-ol			
Oral	DNEL,long term (c	chronic) - systemic effects	26 mg/kg bw/day (Consumer)	
Dermal	DNEL,long term (c	chronic) - systemic effects	319 mg/kg bw/day (Consumer)	
			888 mg/kg bw/day (Employee)	
Inhalative	nhalative DNEL,long term (chronic) - systemic effects		89 mg/m3 (Consumer)	
		500 mg/m3 (Employee)		
PNECs				
67-63-0 pr	opan-2-ol			
PNEC,fresh water		140.9 mg/l (aquatic orga	nism)	
PNEC,marine water 140.9 m		140.9 mg/l (aquatic orga	nism)	
PNEC, fresh water sediment 552 mg/kg (aquatic org.		nism)		
PNEC, marine water sediment 552 m		552 mg/kg (aquatic orga	nism)	
PNEC,soil 28 mg/kg (terrestrial o		28 mg/kg (terrestrial org	anism)	

- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- · Respiratory protection: Not required.
- Protection of hands:



If prolonged or repeated contact is likely, chemical resistant gloves are recommended.

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Safety glasses if risk of splashes.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid

Colour: According to product specification

· Odour: Characteristic

· pH-value: Not applicable.

· Change in condition

Melting point/freezing point: Undetermined. **Initial boiling point and boiling range:** 154-193 °C

· Flash point: 39 °C

· Flammability (solid, gas): Not applicable.

· Auto-ignition temperature: 240 °C

(Contd. on page 5)

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

	(Contd. of page
· Decomposition temperature:	Not determined.
· Explosive properties:	Product is not explosive. However, formation of explosive air vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	7 Vol %
· Oxidising properties	No further relevant information available.
· Vapour pressure at 20 °C:	2 hPa
· Density at 20 °C:	0.84 g/cm^3
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 40 °C:	$<20.5 \text{mm}^2\text{/s}$
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability Stable under recommended storage and handling conditions (see section 7).
- · 10.3 Possibility of hazardous reactions

Dangerous reactions are not expected if the product is handled according to its intended use.

- · 10.4 Conditions to avoid Keep away from sources of ignition No smoking.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No decomposition if used according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	vant for classification:
Hydrocarb	ons, C9-C	11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	>5,000 mg/l (rat)
Hydrocarb	ons, C10-	C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
67-63-0 pr	opan-2-ol	
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50/6h	>25 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

(Contd. on page 6)

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

(Contd. of page 5)

- Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1263
· 14.2 UN proper shipping name	
· ADR	1263 PAINT RELATED MATERIAL
· IMDG, IATA	PAINT RELATED MATERIAL
· 14.3 Transport hazard class(es)	

- · 14.3 Transport hazard class(es)
- · ADR, IMDG, IATA



· Class · Label	3 Flammable liquids.
· 14.4 Packing group · ADR, IMDG, IATA	None. III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number:	Warning: Flammable liquids. 30 F-E, <u>S-E</u>
	(C. 11 7)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, as ammended by Regulation (EU) no. 2015/830

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

	(Contd. of p
Stowage Category	A
14.7 Transport in bulk according to Ann	nex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
- · · -	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 8)

Printing date 08.02.2021 Version: 1.2 Revision: 08.02.2021

(Contd. of page 7)

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.