



Lubricating Wax

- Lubricates tools and machinery
- Keeps working parts moving freely
- Helps reduce resin build-up from softwood
- Reduces corrosion on all bare metal surfaces
- Silicone free



USAGE

Interior

COVERAGE

1 L
10-12 m²

APPLICATION

Brush or
Cotton Cloth

DRYING TIME

Minimum 10
minutes

TOOL CLEANING

White Spirit

Product use

Liberon Lubricating Wax is specially formulated to lubricate and clean saw blades, cutter blades, machine table, lathes, planers, veneer presses and G-clamps to increase efficiency and longevity.

Its special properties will inhibit the formation of rust and assist in the quick cleaning and easy removal of glue from veneer presses and G-clamps.

Preparation

Shake well before use. Ensure the surface is clean, dry and free from rust. Remove rust using Liberon Rust Remover.

Application

Apply a thin coat of Lubricating Wax using a brush or clean cotton cloth. Allow to dry before use. Re-apply as required.

Important: Ensure all working machinery is switched off and stationary before using Liberon Lubricating Wax. Allow to dry before switching equipment on.

Maintenance

Use are required to keep tools and machinery in good condition.

Packaging

Lubricating Wax is available in 500 ml and 1 L containers.

Health and Safety

Harmful. Contains aliphatic solvents. Flammable. Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking. Keep out of the reach of children. Do not empty into drains. Use only in well-ventilated areas. If swallowed do not induce vomiting: seek medical advice immediately and show this container or label.

For further information on this or other Liberon products please contact Liberon Technical Services on 01797 361136.